



RTR Companies, Inc
 203 11th Ave
 PO Box 74
 Orion, IL 61273
 Phone 309-781-9004
<https://www.rtrco.us/>
 rtrco@outlook.com

Now available at RTR Companies! The best fuel solution for all your racing needs. RTR Companies is excited to join forces with Base Racing Fuels & Oils to bring several new racing products to the area for this coming race season. Check with us for current pricing and availability.

Base Leaded Race Fuels



BASE R15 THE ULTIMATE ALL PURPOSE RACE FUEL. FOR ALL TYPES OF MOTORSPORTS. SUPERIOR TO 110 OCTANE FUELS. UP TO 14.1 COMPRESSION.

BASE RACING FUEL	R15
Anti-Knock Index, (R+M)/2	111.0
Motor Octane Number	109.0
Research Octane Number	113.0
Specific Gravity at 60/60 °F	0.71
Vapor Pressure, psia	5.0
Lead Content	Leaded
Color	Blue
Typical Compression Usage	14.0 :1



BASE R16 OUR ORIGINAL COMPRESSION FUEL. USED EXTENSIVELY FOR DIRT MODIFIEDS. FOR ALL TYPES OF RACING. UP TO 14.5 :1 COMPRESSION.

BASE RACING FUEL	R16
Anti-Knock Index, (R+M)/2	112.6
Motor Octane Number	110.8
Research Octane Number	114.4
Specific Gravity at 60/60 °F	0.71
Vapor Pressure, psia	4.8
Lead Content	Leaded
Color	Blue
Typical Compression Usage	14.5 :1



BASE R18 IS DESIGNED FOR HIGH COMPRESSION DIRT LATE MODEL ENGINES. TYPICALLY WIDE BORE, BIG CUBIC INCH, 15:1 COMPRESSION.

BASE RACING FUEL	R18
Anti-Knock Index, (R+M)/2	115.0
Motor Octane Number	113.5
Research Octane Number	116.5
Specific Gravity at 60/60 °F	0.71
Vapor Pressure, psia	4.5
Lead Content	Leaded
Color	Blue
Typical Compression Usage	15.5 :1



BASE R21 THE HIGHEST MOTOR OCTANE FUEL AVAILABLE. USE WITH NITROUS BIG CUBIC INCH DRAG MOTORS. USE FOR ALL COMPRESSION RATES TO 16.5 :1

BASE RACING FUEL	R21
Anti-Knock Index, (R+M)/2	119.0
Motor Octane Number	118.0
Research Octane Number	120.0
Specific Gravity at 60/60 °F	0.70
Vapor Pressure, psia	4.0
Lead Content	Leaded
Color	Blue
Typical Compression Usage	16.5 :1

Base Racing Alcohols



BASE R85 IS A RACING ETHANOL BLEND WITH FULLY LEADED HIGH OCTANE BASE STOCKS. USED EXTENSIVELY FOR CRATE LATE MODELS AND SPORTSMAN ENGINES. FOR COMPRESSION RATES UP TO 14.0 :1

BASE RACING FUEL	R85
Anti-Knock Index, (R+M)/2	114.4
Motor Octane Number	103.9
Research Octane Number	124.9
Specific Gravity at 60/60 °F	0.78
Vapor Pressure, psia	3.7
Lead Content	Leaded
Color	Lt. Blue
Typical Compression Usage	14.0 :1



BASE RM12 IS PURE RACING METHANOL BLENDED WITH COMBUSTION IMPROVERS, TOP LUBE AND FULL RACE PACKAGE OF ADDITIVES. USED EXTENSIVELY FOR DRAG RACING AND SPRINT CARS.

BASE RACING FUEL	RM12
Anti-Knock Index, (R+M)/2	115.5
Motor Octane Number	104.0
Research Octane Number	127.0
Specific Gravity at 60/60 °F	0.79
Vapor Pressure, psia	4.6
Lead Content	Alcohol
Color	BlueTint
Typical Compression Usage	15.0 :1

Base Oxygenated Race Fuel



BASE X04 IS AN OXYGENATED LEVEL 4 LEADED RACE FUEL. USED EXTENSIVELY FOR CRATE LATE MODELS AND AS A POWER SPORTS FUEL. USE FOR COMPRESSION RATES UP TO 13.5 :1

BASE RACING FUEL	X-0-4
Anti-Knock Index, (R+M)/2	110.8
Motor Octane Number	108.1
Research Octane Number	113.5
Specific Gravity at 60/60 °F	0.71
Vapor Pressure, psia	5.4
Lead Content	Leaded
Color	Blue
Typical Compression Usage	13.5 :1

Several engine oil and gear lube options as well as Hollander cleaners are also available.